

ImagePerfect™ 3500 Intermediate Film (FR)

ImagePerfect™ 3500 Intermediate Film is a high-quality, medium-life, matt vinyl range with a semi-permanent solvent-based adhesive. This range is available in black, white, clear and 30 colours.

ImagePerfect™ 3500 Intermediate Film is suitable for a wide variety of indoor and medium-term outdoor applications, such as general purpose signage, decorative panels, directional signage, medium-life outdoor advertising, point-of-sale displays, fleet marking, public transport advertising, etc. The specially-formulated, flexible films can be cut easily and weeded quickly. A semi-permanent, solvent-based adhesive creates a reasonable final bond to ensure a secure, but semi-permanent finish. The inherent properties of the products promote excellent cutting and weeding characteristics because of the high-quality, PE-coated, silicone liner. For white vinyl, a light blue silicone liner is used to form a stronger contrast to lettering.

Specifications	
Description	Intermediate film
Colour	Black, white, clear and 30 colours, matt
Thickness	75mym
Weight	N/A
Adhesive	Solvent based acrylic, semi-permanent
Adhesive Strength	15N/25mm (Finat TM 1/24h)
Release Paper	PE-coated silicone liner, 140g/m ² , white vinyl with blue contrast liner
Temperature Range	-30°C to +90°C
Durability (unprinted)	6 years (black and white) 4 years (clear, colours and metallics)
Flame Retardancy	B1
Shelf Life	2 years, 20°C / 50% humidity
End of Life / Disposal	Not currently recyclable. Can be used for refuse derived fuel (RDF)

© May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom

Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of such products for their specific use, including, but not limited to, the application, conditions, maintenance, and the Purchaser shall assume all risk and liability of every nature in connection therewith. All technical data are subject to change without prior notice. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.

Eikon gives no express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of fitness for any particular use and/or non-infringement. All products are sold subject to Eikon's general terms and conditions of sale. Eikon's aggregate liability, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoiced to Purchaser in respect of any occurrence or series of occurrences. In the event of improper use and/or incorrect processing that does not comply with our instructions, any and all liability is excluded. In no circumstances shall Eikon be liable for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.